

Edilkamin S.p.A. 20020 Lainate (MI), via P. Mascagni 7 Tel. +39 02 937621 Fax +39 02 93762 400/300 mail@edilkamin.com www.edilkamin.com Capitale € 4.100.000 int. vers.
Sede legale:
20123 Milano, via Vincenzo Monti 47
Reg. Imp. di Milano 00192220192
REA n° 878888
Cod. Fiscale e Partita IVA 00192220192

Declaration of performance

According to Regulation (EU) No. 305/2011 N. EK206

| 1. | Unique identification code of the product-type | WIDRO 85 |
|----|---|---|
| 2. | Intended uses of the product in accordance with the applicable harmonized technical specification | Insert or open fireplace by solid fuel (wood logs) , with hot water production |
| 3. | Name or trade mark of the manufacturer (Article 11-5) | EDILKAMIN S.p.A. Via Mascagni, 7 – 20020 Lainate (MI) tel. 02 937621 – mail@edilkamin.com |
| 4. | Name and address of the agent (Article 12-2) | |
| 5. | Assessment and verification system for constancy of | System 3 |

performance (Annex 5)
6a. Harmonized technical specification

EN 13229:2001/A1:2003/A2:2004/AC:2006/AC:2007 ACTECO SrI - NB1880

Laboratory notified

| Declared performance | | | |
|--|-------------------------------------|-------------------|--|
| Essential characteristics | sential characteristics Performance | | |
| Reaction to fire A1 | | A1 | |
| Distance to combustible materials | Distance to combustible materials | | |
| (minimum distance in mm) | R_ Sic | Sides = 0 | |
| | Fron | t = 2000 | |
| | Ceilir | ng = NPD | |
| | 5 ♥FI Floor = NPD | | |
| Risk of burning fuel falling out | Pass | | |
| Emission of combustion products | Rated fuel load | Reduced fuel load | |
| CO (ref. at 13% O ₂) | 856 mg/Nm³ - 0,005% | | |
| NOx (ref. at 13% O ₂) | 112 mg/Nm ³ | _ | |
| OGC (ref. at 13% O ₂) | 64 mg/Nm ³ | | |
| Particulate matter (ref. at 13% O ₂) | 13 mg/Nm ³ | | |
| Electrical safety | | NPD | |
| Cleanability | Pass 3 bar Pass | | |
| Maximum operating pressure | | | |
| Mechanical resistance (to carry a chimneyflue) | | | |
| Thermal output | Rated fuel load | Reduced fuel load | |
| Nominal heat output | 29,7 kW | _ | |
| Nominal space heating output | 11,5 kW | - | |
| Nominal boiler output (to water) | 18,2 kW | | |
| Energy efficiency | 85,7 % | • | |
| Flue gas temperature | T[238°C] | - | |

8. Test report number (based on System 3)

1880-CPR-009-21

The performance of the product identified in point 1 is in conformity with the declared performance in points 6a and 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Lainate, 17/02/2021

Signed for and on behalf of Edilkamin S.p.A. by:

General Manager